



DSV™ Test Stand

FOR ONBOARD RIG PRESSURE TESTING OF PRESSURE CONTROL SUBS - SAFETY VALVES, IBOPs, GRAY VALVES, KELLY COCKS, POP OFF VALVES AND PLUG VALVES.

- > Tests off-line in parallel with BOP testing or drilling
- > Saves 2-3 hours during a routine rig BOP test



THE DSV TEST STAND PROVIDES A QUICK, EASY, PRE-DEFINED AND SAFE METHOD OF TESTING ALL DRILL STEM VALVES PRIOR TO INSTALLATION IN THE STRING.

Now installed on many drilling rigs, the DSV Test Stand is designed for easy operation:

- > 15,000 psi Maximum Working Pressure
- > Requires only a Chain Tong for make-up and break-out of X-Overs and Valves
- > Avoids the use of Rotary Table, Rig Tongs or Iron Roughneck
- > Compact Design
- > Interchangeable X-Overs available for all Rotary Threads
- > Non-Rotate feature



TEST PUMP

- > Test Pump with Integral Chart Recorder, designed for optimum use of the DSV Test Stand - compact, reliable and easy to use.
- > Rig Air 100 psi

THE DSV TEST STAND WILL ENHANCE YOUR RIG'S CAPABILITY, IMPROVE SAFETY AND REDUCE COSTS FOR YOU AND YOUR OPERATOR.

Sub-drill
Endeavour Drive
Arnhall Business Park
Westhill
Aberdeenshire
AB32 6UF
Scotland, UK

Tel: +44 (0)1224 724 600
Fax: +44 (0)1224 744 499
E-mail: sales@subdrill.co.uk
sub-drill.com

